

FEATURES

- High Resolution 5" Digital TFT LCD
- Free Input voltage (DC 10V ~ 30V)
- LED Backlight technology (250cd/m2)
- Capacitive Touch Key
- Shutter camera support
- 2 Camera Inputs
- 2 Trigger Inputs
- Tamperproof function
- Anti Reflection Window
- Automatic Brightness Control
- Auto Scan function
- Auto Power ON/OFF
- NTSC/PAL Auto Switch
- Multi-lingual OSD control
- Built-in Speaker
- Electronic Distance Marker (Parking line)
- Bracket rails and Heavy Duty mounting possibility
- Speedswitch function via tacho signal (in case of frontview purpose)
- Sunvisor – included



Specifications

Power input	10V~30V DC
Video System	NTSC, PAL signal Compatible
Panel	5" Digital
Resolution	640(H) X 480(V) X RGB
Format	4:3
Brightness	250cd/m2
Contrast Ratio	500:1
Display Mode	Single
Speaker	8 ohm/0.3Watt
Viewing Angle	Top: 50°, Bottom: 70°, Left: 70°, Right: 70°
Operating Temperature	-35°C ~ 80°C
Dimensions	148(W) X 104(D) X 29(H)mm
Weight	Approx. 500g
Accessories	- Bracket (Rail Type) - Screw kit - Sunvisor - Instruction manual