

PRO-COM150-HDAR-4/...

4-Channel 19

- > An integrated single tray combining solution housing a 4-channel hybrid TX hybrid combiner, duplex filter, active RX multicouplers and preselector.
- > Minimal rack space required - only 3 HU.


DESCRIPTION

- > Compatible with digital 6.25 kHz channel spacing.
- > Single TX isolators fitted as standard (dual isolators available as option).
- > 4 RX ports as standard.
- > Please specify TX / RX frequencies when ordering.

SPECIFICATIONS

ELECTRICAL	
MODEL	PRO-COM150-HDAR-4/...
FREQUENCY RANGE	l: 136 - 156 MHz h: 152 - 175 MHz
MAX. INPUT POWER PER CH	50 W
MAX. TX-TX SPACING, Δ TX	1.5 MHz
MIN. TX-RX SPACING	4 MHz
INSERTION LOSS - TX PATH	< 8.0 dB
TX-TX ISOLATION	> 70 dB
ANT-TX ISOLATION	> 40 dB @ 25° C
RX ISOLATION IN TX TX-TX spacing < 0.5 MHz TX-TX spacing > 0.5 MHz	> 80 dB > 60 dB
TX ISOLATION IN RX RX-RX spacing < 0.5 MHz RX-RX spacing > 0.5 MHz	> 80 dB > 60 dB
RX-RX ISOLATION	> 20 dB
IMPEDANCE	Nom. 50 Ω
SWR	≤ 1.5
LNA NOISE FIGURE	< 3.5 dB
GAIN - RX PATH	1 dB +/- 1 dB (factory set)
CURRENT CONSUMPTION	500 mA @ 12 VDC

MECHANICAL	
TEMP. RANGE	-30° C → +60° C
CONNECTORS	N-female
DIMENSIONS	19" x 3 HU x 500 mm (483 x 133 x 500 mm)
WEIGHT	Approx. 7.5 kg



ORDERING DESIGNATIONS

TYPE	PRODUCT NO.
PRO-COM150-HDAR-4/l	210001857
PRO-COM150-HDAR-4/h	210001856
PRO-COM150-BHDAR-4/l (With black frontplate)	210002342
PRO-COM150-BHDAR-4/h (With black frontplate)	210002343
ACCESSORIES	
ADAPTOR AC/DC 12V EU	240000040
ADAPTOR AC/DC 12V UK	240000041

ADAPTOR AC/DC 12V EU



ADAPTOR AC/DC 12V UK



ADAPTOR AC/DC 12V EU



ADAPTOR AC/DC 12V UK

