



# DP 3400/3401

## Non-display Portable Radios



- 1 Tri-color LED indicator for clear, visible feedback of calling, scanning and monitoring.
- 2 Emergency button to alert supervisor or dispatcher in an emergency situation.
- 3 New accessory connector meets IP57 submersibility specifications and incorporates RF, USB and enhanced audio capability.
- 4 DP 3401 includes integrated GPS module.
- 5 Radio housing meets IP57 specifications; submersible in 1 metre of water up to 30 minutes.
- 6 Powerful, front projecting speaker.
- 7 Three side programmable buttons for easy access to favourite features. New features such as one-touch calling and quick text messaging are made even easier through programmable button access.
- 8 Large, textured push-to-talk button. Provides good tactile response and easy access, even when wearing gloves.
- 9 32 channels.

### Non-display Portable Radio Standard Package

- Non-display Portable Radio
- Antenna - Standard whip included with DP 3400; GPS Monopole included with DP 3401
- NiMH 1300 mAh Battery
- IMPRES™ Single Unit Charger
- 2.5" Belt Clip
- Quick Reference Guide

### Additional Features

- Enhanced call management
  - Encode: emergency, push-to-talk ID
  - Decode: radio check, remote monitor, radio disable, all call
- Dual-mode analogue/digital scan - facilitates a smooth migration from analogue to digital
- Send quick text messaging via programmable buttons
- DP 3401 can transmit GPS coordinates

## MOTOTRBO™ System Components and Benefits

### DP 3400/3401 Non-display Portable Radios

## Specifications

### GENERAL SPECIFICATIONS

Channel Capacity	32
Frequency	136-174 MHz (VHF) 403-470 MHz (UHF1) 450-512 MHz (UHF2)
Dimensions (HxWxL)	
with NiMH Battery 1300mAh	131.5 x 63.5 x 37.2 mm
with Lilon Std Battery 1500mAh	131.5 x 63.5 x 35.2 mm
with Lilon HiCap Battery 2200mAh	131.5 x 63.5 x 39.2 mm
with Lilon FM Battery 1400mAh	131.5 x 63.5 x 37.2 mm
Weight	
with NiMH Battery	400 g
with Lilon FM Battery	340 g
with Lilon HiCap Battery	345 g
with Lilon Std Battery	330 g
Power Supply	7.2V nominal
Average battery life at 5/5/90 duty cycle with battery saver enabled in carrier squelch and transmitter in high power.	
IMPRES Lilon Std Battery	Analogue: 9 hrs / Digital: 13 hrs
IMPRES Lilon HiCap Battery	Analogue: 13.5hrs / Digital: 19 hrs
IMPRES FM Lilon Battery	Analogue: 8.5 hrs / Digital: 12 hrs
NiMH Battery	Analogue: 8 hrs / Digital: 11 hrs

### RECEIVER

Frequency	136-174 MHz (VHF) 403-470 MHz (UHF1) 450-512 MHz (UHF2)
Channel Spacing	12.5 kHz/ 20 kHz/ 25 kHz
Frequency Stability	+/- 1.5 ppm (DP 3400) ( -30° C, +60° C, +25° C)
Analogue Sensitivity	0.35 uV (12 dB SINAD) 0.22 uV (typical) (12 dB SINAD) 0.4 uV (20 dB SINAD)
Digital Sensitivity	5% BER: 0.3 uV
Intermodulation	65 dB
Adjacent Channel Selectivity	60 dB @ 12.5 kHz, 70 dB @ 20/25 kHz
Spurious Rejection	70 dB
Rated Audio	500 mW
Audio Distortion @ Rated Audio	3% (typical)
Hum and Noise	-40 dB @ 12.5 kHz -45 dB @ 20/25 kHz
Audio Response	+1, -3 dB
Conducted Spurious Emission	-57 dBm

### MILITARY STANDARDS

	810E	Methods	Procedures	810F	Methods	Procedures
Applicable MIL-STD						
Low Pressure	500.3		II	500.4		II
High Temperature	501.3		I/A, II/A1	501.4		I/Hot, II/Hot
Low Temperature	502.3		I/C3, II/C1	502.4		I/C3, II/C1
Temperature Shock	503.3		I/A, 1C3	503.4		I
Solar Radiation	505.3		I	505.4		I
Rain	506.3		I,II	506.4		I, III
Humidity	507.3		II	507.4		-
Salt Fog	509.3		I	509.4		I
Dust	510.3		I	510.4		I
Vibration	514.4		I/10, II/3	514.5		I/24
Shock	516.4		I, IV	516.5		I, IV

**FACTORY MUTUAL APPROVALS** - DP family of radios are certified by Factory Mutual Approvals as intrinsically safe for use in Division 1, Class I,II,III, Groups C,D,E,F,G, when ordered with the Factory Mutual approved battery option.

For more information please contact your local Motorola Authorised Dealer or Distributor

### TRANSMITTER

Frequency	136-174 MHz (VHF) 403-470 MHz (UHF1) 450-512 MHz (UHF2)
Channel Spacing	12.5 kHz/ 20 kHz/ 25 kHz
Frequency Stability	+/- 1.5 ppm (DP 3400) ( -30° C, +60° C, +25° C)
Power Output	UHF1 and UHF2 1W and 4 W VHF 1W and 5 W
Modulation Limiting	+/- 2.5 kHz @ 12.5 kHz +/- 4 kHz @ 20 kHz +/- 5.0 kHz @ 25 kHz
FM Hum and Noise	-40 dB @ 12.5 kHz -45 dB @ 20/25 kHz
Conducted / Radiated Emission	-36 dBm < 1 GHz -30dBm > 1GHz
Adjacent Channel Power	-60 dB @ 12.5 kHz -70 dB @ 20/25 kHz
Audio Response	+1, -3 dB
Audio Distortion	3%
Digital Vocoder Type	AMBE+2
Digital Protocol	ETSI-TS 102 361-1, 2 & 3

### GPS

Accuracy specs are for long-term tracking (95th percentile values > 5 satellites visible at a nominal -130 dBm signal strength)	
TTF (Time To First Fix) Cold Start	< 2 minutes
TTF (Time To First Fix) Hot Start	< 10 seconds
Horizontal Accuracy	< 10 meters

### ENVIRONMENTAL SPECIFICATIONS

Operating Temperature*	-30° C / +60° C
Storage Temperature	-40° C / +85° C
Temperature Shock	Per MIL-STD
Humidity	Per MIL-STD
Water Intrusion	EN60529 - IP57
Packaging Test	MIL-STD 810D and E
* With Lilon battery, operating temperature specification is -10° C / +60° C. With NiMH battery, operating temperature specification is -20° C / +60° C	



MOTOROLA and the Stylised M Logo are registered in the US Patent & Trademark Office. All other product or service names are the property of their respective owners. © Motorola, Inc. 2008. All rights reserved. Conforms to ETSI TS 102 361 (Parts 1, 2 & 3) - ETSI DMR Standard. Specifications subject to change without notice. MOTOTRBO will be launched with a phased introduction - please check availability of products in your region before ordering. All specifications shown are typical. Radio meets applicable regulatory requirements.

DP3400/3401/SPEC-ENG(07/08)

[www.motorola.com](http://www.motorola.com)

Motorola, Ltd. Jays Close, Viabes Industrial Estate, Basingstoke, Hampshire, RG22 4PD, UK